

Recessed downlight-Fixed

Shine series



Description:

Project: _____

Location: _____

Fixture Ref.: _____

Quantity: _____

Remarks: _____


Picture:

Specifications:

Indoor/Outdoor	Indoor
Product No.:	ADLXY07501
Input Voltage:	220-240Vac / 50-60 Hz
System Power:	9W / 12W / 15W
Type of light source:	COB LED
Color Rendering(CRI):	Ra 80 / Ra 90 SDCM<3
CCT:	2700K / 3000K / 3500K / 4000K
System Lumen:	630 lm / 900 lm /1050 lm
System Efficacy:	70 lm/W
Light Distribution:	Direct
Beam Angle:	24° / 36° / 50°
UGR (4H 8H):	UGR<19
IP Rating:	IP44
Color:	RAL9016 White / RAL9005 Black
Luminaire Lifetime:	50.000h (L80B50, Ta25°C)
Working Temperature:	-15 ~ +45 °C
Material:	Die casting aluminum
Electrical Class	III
Photobiological Safety:	Risk Group 1
Dimming:	ON-OFF, TRIAC, 1-10V, DALI



Line Drawings:



Mounting / Connection:

Mounting:	Recessed, Indoor
Cut-out:	75 mm
Connection:	

Packaging Information:

N.W. Fixture (Kg)

G.W. Carton

Mater Carton Dimension:

Qty per Carton:

Photometrics

Please download from the website or consult the sales manager.

Ordering Information:

Model No.	Trim Shape	Product Type	Cut-out	Wattage	Color Rendering	CCT	Beam	Secondary Reflectors	Dimming Options
ADLXY05501	R Round		55	7W	8 80+ CRI	27 2700K			F ON-OFF
ADLXY07501		F Fixed	75	9W	9 90+ CRI	30 3000K	NS (24°)	M Matt	P PHASE DIM
				12W	X 95+ CRI	35 3500K	MB (36°)	W White	V 1~10V DIM
				15W		40 4000K	MF (50°)	B Black	D DALI DIM
ADLXY09501			95	18W					
				24W					

AMAZ reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly.


Product Variants

Shine series-Fixed


Sub-Range	Trim Style	Product Type	Cut-out	System W	Color Rendering	CCT	Beam	LED current	Delivered lumen
ADLXY05501	Trimmed	Fixed	55mm	7W	Ra>90	2700K/3000K/3500K/4000K	24D/36D/50D	150mA	500 lm
ADLXY07501	Trimmed	Fixed	75mm	9W	Ra>90	2700K/3000K/3500K/4000K	24D/36D/50D	200mA	650 lm
	Trimmed	Fixed		12W	Ra>90			300mA	900 lm
	Trimmed	Fixed		15W	Ra>90			350mA	1100 lm
ADLXY09501	Trimmed	Fixed	95mm	18W	Ra>90	2700K/3000K/3500K/4000K	24D/36D/50D	450mA	1300 lm
				24W	Ra>90			600mA	1700 lm




Product Variants-Picture



55mm cut-out
7W



75mm cut-out
10W / 12W / 15W



95mm cut-out
18W / 24W